

# PERFIL (HSS) ESTRUCTURAL

EN LARGOS DE 6.10 y 12.2 METROS

A-500°B LIMITE ELASTICO 46,000 PSI (lb/in<sup>2</sup>)

DIMENSIONES EXTERIORES		ESPESOR		PESO
PULGADA	mm.	PULGADA	mm.	Kg/m
4" x 4"	102 x 102	.375	9.5	25.74
6" x 6"	152 x 152	.187	4.7	21.72
		.250	6.3	28.30
		.312	7.9	34.75
		.375	9.5	40.98
		.500	12.7	52.46
8" x 4"	203 x 102	.187	4.7	21.64
		.250	6.3	28.36
		.375	9.5	40.98
		.500	12.7	52.45
8" x 6"	203 x 152	.250	6.4	33.44
		.375	9.5	48.52
8" x 8"	203 x 203	.187	4.7	28.18
		.250	6.3	38.52
		.312	7.9	47.38
		.375	9.5	56.07
		.500	12.7	72.79
10" x 10"	254 x 254	.187	4.7	36.89
		.250	6.3	48.52
		.312	7.9	60.16
		.375	9.5	71.31
		.500	12.7	92.95
12" x 6"	305 x 152	.375	9.5	63.77
12" x 8"	305 x 203	.375	9.5	71.31
		.500	12.7	92.95
12" x 12"	305 x 305	.250	6.3	58.69
		.312	7.9	72.79
		.375	9.5	86.56
		.500	12.7	113.28
		.625	15.9	138.80
14" x 14"	356 x 356	.375	9.5	101.64
		.500	12.7	133.44
		.625	15.9	163.77
16" x 16"	406 x 406	.375	9.5	116.89
		.500	12.7	153.77
		.625	15.9	189.50

